



## TECHNICAL SPECIFICATIONS

### CENTRAL HEATING COOKER - OIL (Kerosene C2 23 seconds BS 2869 Class 2)

BTUs Max to water	Heat Source	Radiators*	Controls	Flue Pipe Diameter	Minimum vertical rise before bend	Air ventilation to room	Electricity supply
	Cooker 17.6kW Pressure Jet	N/A	Thermostat and internal programmer	127mm 5"	600mm 23 5/8"	166cm <sup>2</sup> 25 1/2in <sup>2</sup>	230-250Hz 7 amp fused
60,000	Boiler 60,000BTU 17.6kW Pressure Jet	12	Wall-mounted Thermostat programmer**	127mm 5"	600mm 23 5/8"	166cm <sup>2</sup> 25 1/2in <sup>2</sup>	230-250Hz 7 amp fused
80,000	Boiler 80,000BTU 23.5kW Pressure Jet	16	Wall-mounted Thermostat programmer**	127mm 5"	600mm 23 5/8"	198cm <sup>2</sup> 30in <sup>2</sup>	230-250Hz 7 amp fused
100,000	Boiler 100,000BTU 29.33kW Pressure Jet	20	Wall-mounted Thermostat programmer**	127mm 5"	600mm 23 5/8"	230cm <sup>2</sup> 32in <sup>2</sup>	230-250Hz 7 amp fused
120,000	Boiler 120,000BTU 35.19kW Pressure Jet	24	Wall-mounted Thermostat programmer**	127mm 5"	600mm 23 5/8"	262cm <sup>2</sup> 36in <sup>2</sup>	230-250Hz 7 amp fused

### CENTRAL HEATING COOKER - GAS (Natural Gas only)

BTUs Max to water	Heat Source	Radiators*	Controls	Flue Pipe Diameter	Minimum vertical rise before bend	Air ventilation to room	Electricity supply
	Cooker 17.6kW Gas Blown	N/A	Thermostat and internal programmer	127mm 5"	600mm 23 5/8"	141cm <sup>2</sup> 22in <sup>2</sup>	230-250Hz 7 amp fused
60,000	Boiler 60,000BTU 17.6kW Gas Blown	12	Thermostat remote programmer supplied by others	127mm 5"	600mm 23 5/8"	141cm <sup>2</sup> 22in <sup>2</sup>	230-250Hz 7 amp fused
80,000	Boiler 80,000BTU 23.5kW Gas Blown	16	Thermostat remote programmer supplied by others	127mm 5"	600mm 23 5/8"	170cm <sup>2</sup> 26 1/4in <sup>2</sup>	230-250Hz 7 amp fused
100,000	Boiler 100,000BTU 29.33kW Gas Blown	20	Thermostat remote programmer supplied by others	127mm 5"	600mm 23 5/8"	199cm <sup>2</sup> 30 3/4in <sup>2</sup>	230-250Hz 7 amp fused
120,000	Boiler 120,000BTU 35.19kW Gas Blown	24	Thermostat remote programmer supplied by others	127mm 5"	600mm 23 5/8"	228cm <sup>2</sup> 35 1/4in <sup>2</sup>	230-250Hz 7 amp fused

\*Number of radiators quoted is based on an average radiator consumption of 5,000BTUs.

\*\*This can be supplied by your dealer.

N.B: Central Heating programmer will need to be supplied by your installer subject to your specifications.